

WatchDog® Accessories & Communication Options

Accessories



Tripod Mount

Rugged galvanized steel folding tripod and 3 ft (1 m) pole
3396TPS **Tripod Mount with Ground Stakes**
3396TP **Tripod Mount without Ground Stakes**

Bird Guard

Reduce debris and maintenance. Improve accuracy. Adjustable to fit 8" diameter rain collectors
3665BG **Bird Guard**

Radiation Shield

Protect your Micro Station or logger from rain and measurement-distorting solar radiation. Compatible with 1000 Series Micro Stations and A-Series Data Loggers
3663A **Radiation Shield**

Sliding Enclosure

Water resistant - mounts to pole or post. Compatible with 1000 Series Micro Stations
3658A **Sliding Enclosure**

Waterproof Enclosure

Clamshell enclosure. Compatible with 1000 Series Micro Stations (Models 1400 or 1200, plus soil sensors)
3659WD1 **Waterproof Enclosure**

Alarm Output Module

Triggers an external device based on a sensor reading. Compatible with WatchDog 2000 Series Stations (Full and Mini)
3672 **Alarm Output Module**

Communication Options



3679WD1

Mid Range Wireless Communications - up to 2 mi (3 km)

Experience the advantages of real-time weather information by connecting your 2000 Series Remote Weather Stations to a PC up to 2 mi (3 km) away (requires line of sight from Station to Base). Base station features a weatherproof case and 50 ft (15 m) cable (terminating in a 9-pin serial connection) to allow high mounting for the greatest range. Remotes include whip antenna, solar panel, and rechargeable batteries. 900 MHz

3393B **Mid Range Wireless Base Station**
3393W **Mid Range Wireless for Remote Station**

Optional Yagi antennas increase line of sight range to 7 mi (11 km); see website for details

WatchDog® 1000/2000 Series Data Shuttle

Transport weather data from your 2000 Series Stations or 1000 Series Micro Stations to your host PC. Holds data for multiple stations (up to 5 Full, 10 Mini, or 12 Micro Stations). Includes soft-sided case (also available separately as Item 7500, see page 39). Requires SpecWare 9 Basic or Pro.

3679WD1 **WatchDog 1000/2000 Data Shuttle**

Cables & Adapters



3660-75SP

Short Range Modem Pair

Use short-range modems to maintain signal on wired connections up to 4,000 ft (1.2 km). Has 9-pin serial connection on PC end.

3365WD2 **Short Range Modem Pair**

Direct Connect Cables for Weather Stations

Connect your WatchDog Weather Station directly to your PC with a 75 ft (22.8 m) cable. Has 9-pin serial connection on PC end, may require USB adapter (Item 3661U9)


3660-75SP **75 ft (22.8 m) Direct Connect Cable**
Includes surge protectors for both ends of the cable connection

3660DP **75 ft (22.8 m) Powered Direct Connect Cable**
Includes AC adapter; no surge protectors

USB-to-3.5mm-Stereo-Plug Adapter

Connect WatchDog and FieldScout® devices directly to your computer's USB port

3661U **USB-to-3.5mm-Stereo-Plug Adapter**



3661U
(Black cable)

USB-to-9-Pin-Serial Adapter

Connect 9-pin Serial cables (such as Item 3660-75SP) directly to your computer's USB port

3661U9 **USB-to-9-Pin-Serial Adapter**



3661U9
(White cable)