

Model	Vol., l	Inner dimensions, mm			Power, kW	Exterior dimensions, mm *		
		Width	Height	Depth		Width	Height	Depth
Up to 350 °C								
SNOL 125/350	125	500	500	500	6	1230	1430	1060
SNOL 250/350	250	500	1000	500	6	1230	1930	1060
SNOL 420/350	420	700	1000	600	8	1430	1930	1160
SNOL 500/350	500	700	1000	700	8	1430	1930	1260
SNOL 600/350	600	800	1000	800	10	1530	1930	1360
SNOL 700/350	700	800	1000	900	10	1710	1930	1610
SNOL 800/350	800	900	1000	900	14	1810	1930	1610
SNOL 970/350	970	900	1200	900	18	1810	2310	1610
SNOL 1000/350	1000	1000	1000	1000	18	1910	2110	1710
SNOL 1200/350	1200	1000	1200	1000	22	1910	2310	1710
SNOL 1500/350	1500	1000	1500	1000	22	1910	2610	1710
SNOL 2200/350	2200	1000	1500	1500	26	1910	2610	2210
SNOL 2500/350	2500	1000	1700	1500	26	1910	2810	2210
SNOL 3400/350	3400	1000	1700	2000	30	1910	2810	2710
SNOL 4000/350	4000	1200	1700	2000	30	2110	3010	2710
SNOL 4800/350	4800	1200	2000	2000	30	2110	3310	2710
Up to 450 °C								
SNOL 125/450	125	500	500	500	8	1230	1430	1060
SNOL 250/450	250	500	1000	500	10	1230	1930	1060
SNOL 420/450	420	700	1000	600	12	1430	1930	1160
SNOL 500/450	500	700	1000	700	12	1430	1930	1260
SNOL 600/450	600	800	1000	800	16	1530	1930	1360
SNOL 700/450	700	800	1000	900	18	1710	1930	1610
SNOL 800/450	800	900	1000	900	18	1810	1930	1610
SNOL 970/450	970	900	1200	900	21	1810	2310	1610
SNOL 1000/450	1000	1000	1000	1000	21	1910	2110	1710
SNOL 1200/450	1200	1000	1200	1000	24	1910	2310	1710
SNOL 1500/450	1500	1000	1500	1000	24	1910	2610	1710
SNOL 2200/450	2200	1000	1500	1500	35	1910	2610	2210
SNOL 2500/450	2500	1000	1700	1500	35	1910	2810	2210
SNOL 3400/450	3400	1000	1700	2000	45	1910	2810	2710
SNOL 4000/450	4000	1200	1700	2000	55	2110	3010	2710
SNOL 4800/450	4800	1200	2000	2000	55	2110	3310	2710
Up to 650 °C								
SNOL 125/650	125	500	500	500	8	1530	1730	1360
SNOL 250/650	250	500	1000	500	12	1530	2230	1360
SNOL 420/650	420	700	1000	600	16	1730	2230	1460
SNOL 500/650	500	700	1000	700	16	1730	2230	1560
SNOL 600/650	600	800	1000	800	18	1830	2230	1660
SNOL 700/650	700	800	1000	900	18	1830	2230	1760
SNOL 800/650	800	900	1000	900	21	1930	2230	1760
SNOL 970/650	970	900	1200	900	25	1930	2430	1760
SNOL 1000/650	1000	1000	1000	1000	25	2030	2230	1860
SNOL 1200/650	1200	1000	1200	1000	30	2030	2430	1860
SNOL 1500/650	1500	1000	1500	1000	32	2030	2730	1860
SNOL 2200/650	2200	1000	1500	1500	45	2030	2730	2360
SNOL 2500/650	2500	1000	1700	1500	45	2030	2930	2360
SNOL 3500/650	3500	1000	1700	2000	55	2030	2930	2860
SNOL 4000/650	4000	1200	1700	2000	65	2410	3310	3010
SNOL 4800/650	4800	1200	2000	2000	75	2410	3610	3010
Up to 750 °C								
SNOL 125/750	125	500	500	500	16	1530	1730	1360
SNOL 250/750	250	500	1000	500	18	1530	2230	1360
SNOL 400/750	400	700	1000	600	24	1730	2230	1460
SNOL 500/750	500	700	1000	700	24	1730	2230	1560
SNOL 600/750	600	800	1000	800	27	1830	2230	1660
SNOL 700/750	700	800	1000	900	27	1830	2230	1760
SNOL 800/750	800	900	1000	900	32	1930	2230	1760
SNOL 970/750	970	900	1200	900	32	1930	2430	1760
SNOL 1000/750	1000	1000	1000	1000	32	2030	2230	1860
SNOL 1200/750	1200	1000	1200	1000	45	2030	2430	1860
SNOL 1500/750	1500	1000	1500	1000	48	2030	2730	1860
SNOL 2200/750	2200	1000	1500	1500	65	2030	2730	2360
SNOL 2500/750	2500	1000	1700	1500	65	2030	2930	2360
SNOL 3400/750	3400	1000	1700	2000	80	2030	2930	2860
SNOL 4000/750	4000	1200	1700	2000	95	2410	3310	3010
SNOL 4800/750	4800	1200	2000	2000	110	2410	3610	3010

* Overall dimensions can be adjusted
Note: Chamber dimensions can be adjusted subject to customer requirements when ordering