



Model	Vol., l	Inner dimensions, mm			Power, kW	Exterior dimensions, mm*		
		Width	Height	Depth		Width	Height	Depth
Up to 1200 °C								
SNOL 500/1200 BH	500	700	1000	700	50	2200	2800	1900
SNOL 800/1200 BH	800	900	1000	900	52	2400	2800	2100
SNOL 970/1200 BH	970	900	1200	900	72	2400	3000	2100
SNOL 1080/1200 BH	1080	900	1200	1000	72	2400	3000	2200
SNOL 1200/1200 BH	1200	1000	1200	1000	72	2500	3000	2200
SNOL 2200/1200 BH	2200	1000	1500	1500	100	2500	3300	2700
SNOL 3000/1200 BH	3000	1000	1500	2000	140	2500	3300	3200
SNOL 4200/1200 BH	4200	1000	1700	2500	160	2500	3500	3700
SNOL 5100/1200 BH	5100	1200	1700	2500	200	2700	3500	3700
SNOL 9000/1200 BH	9000	1500	2000	3000	240	3000	3800	4200
Up to 1300 °C								
SNOL 500/1300 BH	500	700	1000	700	55	2500	3400	2600
SNOL 800/1300 BH	800	900	1000	900	55	2700	3400	2800
SNOL 970/1300 BH	970	900	1200	900	80	2700	3600	2800
SNOL 1080/1300 BH	1080	900	1200	1000	80	2700	3600	2900
SNOL 1250/1300 BH	1250	1000	1250	1000	80	2800	3650	2900
SNOL 2200/1300 BH	2200	1000	1500	1500	140	2800	3900	3400
SNOL 3000/1300 BH	3000	1000	1500	2000	160	2800	3900	3900
SNOL 4200/1300 BH	4200	1000	1750	2500	200	2800	4150	4400
SNOL 5250/1300 BH	5250	1200	1750	2500	240	3000	4150	4400
SNOL 9000/1300 BH	9000	1500	2000	3000	240	3300	4400	4900

* Overall dimensions can be adjusted
 Note: Chamber dimensions can be adjusted subject to customer requirements when ordering