

Model	Vol., l	Inner dimensions, mm			Power, kW	Exterior dimensions, mm*		
		Width	Height	Depth		Width	Height	Depth
<b>Up to 350 °C</b>								
SNOL 500/350 BH	500	700	1000	700	8	1730	2230	1460
SNOL 800/350 BH	800	900	1000	900	14	1930	2230	1660
SNOL 970/350 BH	970	900	1200	900	18	1930	2430	1660
SNOL 1000/350 BH	1000	900	1200	1000	18	1930	2430	1760
SNOL 1200/350 BH	1200	1000	1200	1000	22	2030	2430	1760
SNOL 2200/350 BH	2200	1000	1500	1500	28	2030	2730	2260
SNOL 3000/350 BH	3000	1000	1500	2000	32	2030	2730	2760
SNOL 4200/350 BH	4200	1000	1700	2500	38	2030	2930	3260
SNOL 5100/350 BH	5100	1200	1700	2500	45	2230	2930	3260
SNOL 9000/350 BH	9000	1500	2000	3000	55	2530	3230	3760
<b>Up to 450 °C</b>								
SNOL 500/450 BH	500	700	1000	700	8	1730	2230	1460
SNOL 800/450 BH	800	900	1000	900	14	1930	2230	1660
SNOL 970/450 BH	970	900	1200	900	18	1930	2430	1660
SNOL 1000/450 BH	1000	900	1200	1000	18	1930	2430	1760
SNOL 1200/450 BH	1200	1000	1200	1000	22	2030	2430	1760
SNOL 2200/450 BH	2200	1000	1500	1500	28	2030	2730	2260
SNOL 3000/450 BH	3000	1000	1500	2000	32	2030	2730	2760
SNOL 4200/450 BH	4200	1000	1700	2500	38	2030	2930	3260
SNOL 5100/450 BH	5100	1200	1700	2500	45	2230	2930	3260
SNOL 9000/450 BH	9000	1500	2000	3000	55	2530	3230	3760
<b>Up to 650 °C</b>								
SNOL 500/650 BH	500	700	1000	700	18	2030	2530	1760
SNOL 800/650 BH	800	900	1000	900	24	2230	2530	1960
SNOL 970/650 BH	970	900	1200	900	24	2230	2730	1960
SNOL 1000/650 BH	1000	900	1200	1000	28	2230	2730	2060
SNOL 1200/650 BH	1200	1000	1200	1000	28	2330	2730	2060
SNOL 2200/650 BH	2200	1000	1500	1500	48	2330	3030	2560
SNOL 3000/650 BH	3000	1000	1500	2000	55	2330	3030	3060
SNOL 4250/650 BH	4250	1000	1700	2500	65	2330	3230	3560
SNOL 5100/650 BH	5100	1200	1700	2500	78	2530	3230	3560
SNOL 9000/650 BH	9000	1500	2000	3000	90	2830	3530	4060
<b>Up to 750</b>								
SNOL 500/750 BH	500	700	1000	700	27	2030	2530	1760
SNOL 800/750 BH	800	900	1000	900	36	2230	2530	1960
SNOL 970/750 BH	970	900	1200	900	36	2230	2730	1960
SNOL 1000/750 BH	1000	900	1200	1000	42	2230	2730	2060
SNOL 1200/750 BH	1200	1000	1200	1000	42	2330	2730	2060
SNOL 2200/750 BH	2200	1000	1500	1500	72	2330	3030	2560
SNOL 3000/750 BH	3000	1000	1500	2000	80	2330	3030	3060
SNOL 4200/750 BH	4200	1000	1700	2500	95	2330	3230	3560
SNOL 5100/750 BH	5100	1200	1700	2500	117	2530	3230	3560
SNOL 9000/750 BH	9000	1500	2000	3000	135	2830	3530	4060

\* Overall dimensions can be adjusted  
Note: Chamber dimensions can be adjusted subject to customer requirements when ordering