



Model	Vol., l	Inner dimensions, mm			Power, kW	Exterior dimensions, mm*		
		Width	Height	Depth		Width	Height	Depth
Up to 250 °C								
SNOL 500/250 Arc	500	700	1000	700	6	1610	1630	1260
SNOL 800/250 Arc	800	900	1000	900	12	1810	1630	1460
SNOL 970/250 Arc	970	900	1200	900	12	1810	1830	1460
SNOL 1000/250 Arc	1000	900	1200	1000	14	1810	1830	1560
SNOL 1200/250 Arc	1200	1000	1200	1000	16	1910	1830	1560
SNOL 2200/250 Arc	2200	1000	1500	1500	18	1910	2130	2060
SNOL 3000/250 Arc	3000	1000	1500	2000	24	1910	2230	2560
SNOL 4200/250 Arc	4200	1000	1750	2500	28	1910	2480	3060
SNOL 5100/250 Arc	5100	1200	1750	2500	32	2110	2480	3060
SNOL 9000/250 Arc	9000	1500	2000	3000	43	2410	2730	3560
Up to 350 °C								
SNOL 500/350 Arc	500	700	1000	700	8	1610	1730	1260
SNOL 800/350 Arc	800	900	1000	900	14	1810	1730	1460
SNOL 970/350 Arc	970	900	1200	900	18	1810	1930	1460
SNOL 1000/350 Arc	1000	900	1200	1000	18	1810	1930	1560
SNOL 1200/350 Arc	1200	1000	1200	1000	22	1910	1930	1560
SNOL 2200/350 Arc	2200	1000	1500	1500	26	1910	2230	2060
SNOL 3000/350 Arc	3000	1000	1500	2000	30	1910	2330	2560
SNOL 4200/350 Arc	4200	1000	1700	2500	36	1910	2530	3060
SNOL 5100/350 Arc	5100	1200	1700	2500	40	2110	2530	3060
SNOL 9000/350 Arc	9000	1500	2000	3000	50	2410	2830	3560

* Overall dimensions can be adjusted
 Note: Chamber dimensions can be adjusted subject to customer requirements when ordering